



DURA-CORE® AND PAA-CORE® METALLIC HONEYCOMB CUSTOMER QUALIFICATIONS CHART

Dura-Core® and PAA-Core® Metallic Honeycomb are offered in a wide range of types, classes, grades, densities for commercial, aerospace, defense, industrial, transportation and non-aerospace applications. The reference chart below lists the primary specifications that we are qualified to. Please contact us for updates and for us to qualify to your specifications.

Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)
Airbus	Dura-Core® - Aluminum 5052 Alloy	AIMS 11-02-001		N	G		3/16" - 3.1 pcf	4.8mm - 50kg/m ³
	Dura-Core® Aluminum Honeycomb	AIMS 11-02-002		N	A		1/8" - 4.5 pcf	3.2mm - 72kg/m ³
	- 5056 Alloy	AIMS 11-02-002		N	R		5/32" - 3.8 pcf	4.0mm - 61kg/m ³
Airbus Helicopters	PAA Aluminum Honeycomb - 5056 Alloy	ECS2449		5056		PAA	5/32" - 3.8 pcf	4.0mm - 61kg/m ³
		ECS2447		5056		PAA	5/32" - 2.6 pcf	4.0mm - 42kg/m ³
		ECS2451		5056		PAA	3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		ECS2450		5056		PAA	3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		ECS2448		5056		PAA	1/4" - 3.4 pcf	6.4mm - 54kg/m ³
Bell Textron	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	299-947-059	IV, V, IX				1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		299-947-059	IV, V, IX, IXa				1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		299-947-059	IV, V, IX, IXa				1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		299-947-059	IV, V, IX, IXa				1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		299-947-059	IV, V, IX, IXa				1/8" - 10.0 pcf	3.2mm - 160kg/m ³
		299-947-059	IV, V, IX, IXa				1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		299-947-059	IV, V, IX				5/32" - 2.6 pcf	4.0mm - 42kg/m ³
		299-947-059	IV, V, IX, IXa				5/32" - 3.8 pcf	4.0mm - 61kg/m ³
		299-947-059	IV, V, IX, IXa				5/32" - 5.3 pcf	4.0mm - 85kg/m ³
		299-947-059	IV, V, IX, IXa				5/32" - 6.9 pcf	4.0mm - 110kg/m ³
		299-947-059	IV, V, IX, IXa				5/32" - 8.4 pcf	4.0mm - 135kg/m ³
		299-947-059	IV, V, IX, IXa				5/32" - 10.0 pcf	4.0mm - 160kg/m ³
		299-947-059	IV, V, IX				3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		299-947-059	IV, V, IX, IXa				3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		299-947-059	IV, V, IX, IXa				3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		299-947-059	IV, V, IX, IXa				3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		299-947-059	IV, V, IX, IXa				3/16" - 6.9 pcf	4.8mm - 110kg/m ³
		299-947-059	IV, V, IX, IXa				3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		299-947-059	IV, V, IX, IXa				3/16" - 10.6 pcf	4.8mm - 170kg/m ³
		299-947-059	IV, V, IX				1/4" - 1.6 pcf	6.4mm - 26kg/m ³
		299-947-059	IV, V, IX, IXa				1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		299-947-059	IV, V, IX, IXa				1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		299-947-059	IV, V, IX, IXa				1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		299-947-059	IV, V, IX, IXa				1/4" - 5.2 pcf	6.4mm - 83kg/m ³
		299-947-059	IV, V, IX, IXa				1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		299-947-059	IV, V, IX, IXa				1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		299-947-059	IV, V				1/4" - 9.2 pcf	6.4mm - 147kg/m ³
		299-947-059	IV, V, IX				3/8" - 1.0 pcf	9.5mm - 16kg/m ³
		299-947-059	IV, V, IX, IXa				3/8" - 1.6 pcf	9.5mm - 26kg/m ³
		299-947-059	IV, V, IX, IXa				3/8" - 2.3 pcf	9.5mm - 37kg/m ³
		299-947-059	IV, V, IX, IXa				3/8" - 3.0 pcf	9.5mm - 48kg/m ³
		299-947-059	IV, V, IX, IXa				3/8" - 3.7 pcf	9.5mm - 59kg/m ³
299-947-059	IV, V, IX, IXa				3/8" - 4.2 pcf	9.5mm - 67kg/m ³		
299-947-059	IV, V, IX, IXa				3/8" - 5.4 pcf	9.5mm - 86kg/m ³		
299-947-059	IV, V				3/8" - 6.5 pcf	9.5mm - 104kg/m ³		
299-947-059	IV, V				3/8" - 7.6 pcf	9.5mm - 122kg/m ³		

NOTES:
Type IV = DURA-CORE® 5052 Aluminum Alloy Core
Type V = DURA-CORE® 5056 Aluminum Alloy Core
Type IX = PAA Phosphoric Acid Anodized, 5052 Aluminum Alloy Core
Type IXa = PAA Phosphoric Acid Anodized, 5056 Aluminum Alloy Core



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)
Boeing	Dura-Core® or PAA Aluminum Honeycomb - 5052 Alloy	BMS4-4	2-07	N,P,ND,NPA	I	ALL	1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		BMS4-4	2-10	N,P,ND,NPA	I	ALL	1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		BMS4-4	2-15	N,P,ND,NPA	I	ALL	1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		BMS4-4	2-20	N,P,ND,NPA	I	ALL	1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		BMS4-4	3-07	N,P,ND,NPA	I	ALL	3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		BMS4-4	3-10	N,P,ND,NPA	I	ALL	3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		BMS4-4	3-15	N,P,ND,NPA	I	ALL	3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		BMS4-4	3-20	N,P,ND,NPA	I	ALL	3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		BMS4-4	3-25	N,P,ND,NPA	I	ALL	3/16" - 6.9 pcf	4.8mm - 110kg/m ³
		BMS4-4	3-30	N,P,ND,NPA	I	ALL	3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		BMS4-4	4-07	N,P,ND,NPA	I	ALL	1/4" - 1.6 pcf	6.4mm - 26kg/m ³
		BMS4-4	4-10	N,P,ND,NPA	I	ALL	1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		BMS4-4	4-15	N,P,ND,NPA	I	ALL	1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		BMS4-4	4-20	N,P,ND,NPA	I	ALL	1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		BMS4-4	4-25	N,P,ND,NPA	I	ALL	1/4" - 5.2 pcf	6.4mm - 83kg/m ³
		BMS4-4	4-30	N,P,ND,NPA	I	ALL	1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		BMS4-4	4-40	N,P,ND,NPA	I	ALL	1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		BMS4-4	6-10	N,P,ND,NPA	I	ALL	3/8" - 1.6 pcf	9.5mm - 26kg/m ³
		BMS4-4	6-20	N,P,ND,NPA	I	ALL	3/8" - 3.0 pcf	9.5mm - 48kg/m ³
		BMS4-4	6-25	N,P,ND,NPA	I	ALL	3/8" - 3.7 pcf	9.5mm - 59kg/m ³
		BMS4-4	6-30	N,P,ND,NPA	I	ALL	3/8" - 4.2 pcf	9.5mm - 67kg/m ³
		BMS4-4	6-40	N,P,ND,NPA	I	ALL	3/8" - 5.4 pcf	9.5mm - 87kg/m ³
		BMS4-4	6-50	N,P,ND,NPA	I	ALL	3/8" - 6.5 pcf	9.5mm - 104kg/m ³
BMS4-4	3-60N	N		II	B	3/32"* - 25.0 pcf	2.36mm - 400kg/m ³	
BMS4-4	3-60	NPA		II, III	B	3/32"* - 25.0 pcf	2.36mm - 400kg/m ³	
Boeing	PAA Aluminum Honeycomb - 5056 Alloy	BMS4-25	6-30	ALL		ALL	3/8" - 4.2 pcf	9.5mm - 67kg/m ³
		BMS4-25	6-40	ALL		ALL	3/8" - 5.4 pcf	9.5mm - 87kg/m ³
		BMS4-25	2-30	ALL		ALL	1/8" - 12.0 pcf	3.2mm - 192kg/m ³
Boeing St. Louis	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	MMS 701, 714, 728	N or P	5052, 5056			1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		MMS 714, 728	N or P	5056			1/8" - 6.1 pcf	3.2mm - 97kg/m ³
		MMS 701, 714, 728	N or P	5052, 5056			1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		MMS 714, 728	N or P	5056			1/8" - 10.0 pcf	3.2mm - 160kg/m ³
		MMS 701, 714, 728	N or P	5052, 5056			1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		MMS 701, 728	N or P	5052, 5056			1/8" - 22.0 pcf	3.2mm - 352kg/m ³
		MMS 714, 728	N or P	5056			5/32" - 3.8 pcf	4.0mm - 60kg/m ³
		MMS 714, 728	N or P	5056			5/32" - 5.3 pcf	4.0mm - 85kg/m ³
		MMS 714, 728	N or P	5056			5/32" - 6.9 pcf	4.0mm - 110kg/m ³
		MMS 701, 714, 728	N or P	5052, 5056			3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		MMS 701, 714, 728	N or P	5052, 5056			3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		MMS 701, 714, 728	N or P	5052, 5056			3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		MMS 701, 714, 728	N or P	5052, 5056			1/4" - 2.3 pcf	6.4mm - 37kg/m ³
MMS 714, 728	N or P	5056			1/4" - 3.4 pcf	6.4mm - 54kg/m ³		
MMS 714, 728	N or P	5056			1/4" - 4.3 pcf	6.4mm - 69kg/m ³		
MMS 701, 728	N or P	5052, 5056			1/4" - 7.9 pcf	6.4mm - 126kg/m ³		
COMAC	PAA Aluminum Honeycomb - 5052 Alloy	CMS-CP-401	I	I	3.1	B	1/8" - 3.1 pcf	3.2mm - 48kg/m ³
		CMS-CP-401	I	I	6.1	B	1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		CMS-CP-401	I	I	8.1	B	1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		CMS-CP-401	V	I	3.1	B	3/16" - 3.1 pcf	4.8mm - 48kg/m ³
Decrane/Pats	Dura-Core® Aluminum Honeycomb - 5052 Alloy	PS-028					1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		This core has to be slotted on both sides						
General Dynamics	Dura-Core® Honeycomb Core - 5052 Alloy	P190	1B				1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		P190	2C				1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		P190	1D				1/8" - 8.1 pcf	3.2mm - 130kg/m ³

NOTES:
Class N = Non-Perforated Core
Class P = Perforated Core
Class ND = Non-Perforated, High Durability Core
Class NPA = Non-Perforated, Phosphoric Acid Anodized and Prime Core
Grade II - for core having a bisected hexagonal cell configuration
Grade III - for core having a bisected half hexagonal cell configuration
3/32"* = bisected 3/16" hexagonal cell configuration

NOTES:
MMS 701 = 5052 Alloy DURA-CORE® Aluminum Honeycomb
MMS 714 = 5056 Alloy DURA-CORE® Aluminum Honeycomb
MMS 728 = 5056 PAA Phosphoric Acid Anodized Honeycomb
TYPE N = Non-Perforated Core
TYPE P = perforated core
5052 and 5056 Aluminum Alloy is shown under CLASS category



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)
General Dynamics (Cont.)	Dura-Core® Honeycomb Core - 5052 Alloy	P190	2A				3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		P190	2B				3/16" - 4.4 pcf	4.8mm - 70kg/m ³
Goodrich	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	RMS 026	1	1,2,3	2		3/64" - 28.0 pcf	1.2mm - 449kg/m ³
		RMS 026	1	1,2,3	2		3/64" - 55.0 pcf	1.2mm - 881kg/m ³
		RMS 026	1	1,2,3	2		3/32" - 25.0 pcf	2.4mm - 400kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/8" - 22.1 pcf	3.2mm - 354kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		5/32" - 2.6 pcf	4.0mm - 42kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		5/32" - 3.8 pcf	4.0mm - 61kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		5/32" - 5.3 pcf	4.0mm - 85kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/16" - 6.9 pcf	4.8mm - 110kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		RMS 026	1	1,2,3	2		3/16" - 16.0 pcf	4.8mm - 256kg/m ³
		RMS 026	1	1,2,3	2		3/16" - 25.0 pcf	4.8mm - 400kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/4" - 1.6 pcf	6.4mm - 26kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/4" - 5.2 pcf	6.4mm - 83kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 1.0 pcf	9.5mm - 16kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 1.6 pcf	9.5mm - 26kg/m ³
		RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 2.3 pcf	9.5mm - 37kg/m ³
RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 3.0 pcf	9.5mm - 48kg/m ³		
RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 3.7 pcf	9.5mm - 59kg/m ³		
RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 4.2 pcf	9.5mm - 67kg/m ³		
RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 5.4 pcf	9.5mm - 86kg/m ³		
RMS 026	1 or 2	1,2,3	1 or 2		3/8" - 6.5 pcf	9.5mm - 104kg/m ³		
Hispano Suiza	PAA Aluminum Honeycomb - 5052 and 5056 Alloy	BLGG 500601					1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		BLGG 500601					1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		BLGG 500601					1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		BLGG 500601					1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		BLGG 500601					1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		BLGG 500601					1/8" - 22.1 pcf	3.2mm - 354kg/m ³
		BLGG 500601					5/32" - 2.6 pcf	4.0mm - 42kg/m ³
		BLGG 500601					3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		BLGG 500601					3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		BLGG 500601					3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		BLGG 500601					3/16" - 6.9 pcf	4.8mm - 110kg/m ³
		BLGG 500601					3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		BLGG 500601					1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		BLGG 500601					1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		BLGG 500601					1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		BLGG 500601					1/4" - 5.2 pcf	6.4mm - 83kg/m ³
BLGG 500601					1/4" - 6.0 pcf	6.4mm - 96kg/m ³		

NOTES:
Type 1 = Honeycomb manufactured from 5052 Aluminum Alloy Foil
Type 2 = Honeycomb manufactured from 5056 Aluminum Alloy Foil
Class 1 = For Acoustic Structures
Class 2 = For Non-Acoustic Structures
Class 3 = For 3/8" cell Acoustic Applications with Slotted Core
Grade 1 = DURA-CORE® corrosion protective coating
Grade 2 = PAA, Phosphoric Acid Anodized protective coating

NOTES:
 Available as perforated and non-perforated core
 Available as PAA, Phosphoric Acid Anodized
 Available in 5052 and 5056 Alloy



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)
Hispano Suiza (Cont.)	PAA Aluminum Honeycomb - 5052 and 5056 Alloy	BLGG 500601					1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		BLGG 500601					3/8" - 2.3 pcf	9.5mm - 36kg/m ³
		BLGG 500601					3/8" - 3.0 pcf	9.5mm - 48kg/m ³
		BLGG 500601					3/8" - 3.7 pcf	9.5mm - 59kg/m ³
		BLGG 500601					3/8" - 4.2 pcf	9.5mm - 67kg/m ³
		BLGG 500601					3/8" - 5.4 pcf	9.5mm - 87kg/m ³
		BLGG 500601					3/8" - 6.5 pcf	9.5mm - 104kg/m ³
		BLGG 500601					3/8" - 7.6 pcf	9.5mm - 122kg/m ³
		BLGG 500801					1/8" - 22.1 pcf	3.2mm - 354kg/m ³
Leonardo	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	MMS 8010	D,P	5052, 5056			1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		MMS 8010	D,P	5052			1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		MMS 8010	D,P	5052			1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		MMS 8010	D,P	5052			1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		MMS 8010	D,P	5052			1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		MMS 8010	D,P	5052			1/8" - 22.1 pcf	3.2mm - 354kg/m ³
		MMS 8010	D,P	5052			3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		MMS 8010	D,P	5052, 5056			3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		MMS 8010	D,P	5052			3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		MMS 8010	D,P	5052			3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		MMS 8010	D,P	5052			3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		MMS 8010	D,P	5052			1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		MMS 8010	D,P	5052			1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		MMS 8010	D,P	5052			1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		MMS 8010	D,P	5052			1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		MMS 8010	D,P	5052			1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		MMS 8010	D,P	5052			3/8" - 4.2 pcf	9.5mm - 67kg/m ³
Lockheed	Dura-Core® Aluminum Honeycomb - 5052 Alloy	FMS 3010					1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		FMS 3010					1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		FMS 3010					1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		FMS 3010					3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		FMS 3010					3/16" - 4.4 pcf	4.8mm - 70kg/m ³
Lockheed	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	STM Y1071	II		C		1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		STM Y1071	II		C		1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		STM Y1071	II		P,C		1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		STM Y1071	I, II		P,C		1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		STM Y1071	I		C		3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		STM Y1071	II		P,C		3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		STM Y1071	II		C		3/16" - 3.4 pcf	4.8mm - 54kg/m ³
		STM Y1071	II		P,C		3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		STM Y1071	I		C		3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		STM Y1071	I		C		1/4" - 1.6 pcf	6.4mm - 26kg/m ³
		STM Y1071	I, II		P,C		1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		STM Y1071	I, II		P,C		1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		STM Y1071	I, II		P,C		1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		STM Y1071	I, II		P		1/4" - 5.2 pcf	6.4mm - 83kg/m ³
STM Y1071	I		C		1/4" - 7.9 pcf	6.4mm - 126kg/m ³		
STM Y1071	I		C		3/8" - 1.0 pcf	9.5mm - 16kg/m ³		
Northrop Grumman	Dura-Core® Aluminum Honeycomb - 5052 Alloy	GC 100B, GC100F			B		1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		GC 100B, GC100F			B		1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		GC 100B, GC100F			B		1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		GC 100B, GC100F			B		1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		GC 100B, GC100F			B		1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		GC 100B, GC100F			B		1/8" - 22.1 pcf	3.2mm - 352kg/m ³
		GC 100B, GC100F			B		3/16" - 3.1 pcf	4.8mm - 50kg/m ³

NOTES:
All available as either **DURA-CORE®**
or **PAA Phosphoric Acid Anodized**

5052 and 5056 Aluminum Alloy is
shown under **CLASS** category

NOTES:
Type I = 5052 Aluminum Alloy
Type II = 5056 Aluminum Alloy
Grade C designates **DURA-CORE®**
Grade P designates **PAA**
Phosphoric Acid Anodized



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)
Northrop Grumman (Cont.)	Dura-Core® Aluminum Honeycomb - 5052 Alloy	GC 100B, GC100F					3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		GC 100B, GC100F					3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		GC 100B, GC100F					3/16" - 6.9 pcf	4.8mm - 110kg/m ³
		GC 100B, GC100F					3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		GC 100B, GC100F					1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		GC 100B, GC100F					1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		GC 100B, GC100F					1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		GC 100B, GC100F					1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		GC 100B, GC100F					1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		GC 100B, GC100F					3/8" - 1.6 pcf	9.5mm - 26kg/m ³
		GC 100B, GC100F					3/8" - 3.0 pcf	9.5mm - 48kg/m ³
		GC 100B, GC100F					3/8" - 4.2 pcf	9.5mm - 67kg/m ³
		GC 100B, GC100F					3/8" - 5.4 pcf	9.5mm - 86kg/m ³
		GC 100B, GC100F					3/8" - 6.5 pcf	9.5mm - 104kg/m ³
Northrop Grumman	Dura-Core® Aluminum Honeycomb - 5052 Alloy	NAI-1171					1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		NAI-1171					1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		NAI-1171					1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		NAI-1171					1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		NAI-1171					3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		NAI-1171					3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		NAI-1171					3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		NAI-1171					3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		NAI-1171					1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		NAI-1171					1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		NAI-1171					1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		NAI-1171					1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		NAI-1171					1/4" - 7.9 pcf	6.4mm - 126kg/m ³
MRAS	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/8" - 10.0 pcf	3.2mm - 160kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/8" - 12.0 pcf	3.2mm - 192kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		5/32" - 2.6 pcf	4.0mm - 42kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		5/32" - 3.8 pcf	4.0mm - 61kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		5/32" - 5.3 pcf	4.0mm - 85kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		5/32" - 6.9 pcf	4.0mm - 110kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/16" - 6.9 pcf	4.8mm - 110kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/4" - 1.6 pcf	6.4mm - 26kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/4" - 5.2 pcf	6.4mm - 83kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		1/4" - 7.9 pcf	6.4mm - 126kg/m ³
STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 1.0 pcf	9.5mm - 16kg/m ³		
STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 1.6 pcf	9.5mm - 26kg/m ³		
STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 2.3 pcf	9.5mm - 36kg/m ³		
STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 3.0 pcf	9.5mm - 48kg/m ³		

NOTES:
 The STMM-Y100 Material Specification is based upon AMS-C-7438
Class 1 = PAA, Phosphoric Acid Anodized - High Corrosion Resistance
Class 2 = DURA-CORE®, Standard Corrosion Resistance
Type N = Non-Perforated Core
Type P = Perforated Core



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)
MRAS (Cont.)	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 3.7 pcf	9.5mm - 59kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 4.2 pcf	9.5mm - 67kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 5.4 pcf	9.5mm - 87kg/m ³
		STMM-Y100	Type N or Type P	Class 1 or Class 2	B		3/8" - 6.5 pcf	9.5mm - 104kg/m ³
Raytheon	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	BS 25017		1 or 2	1 or 2		1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		BS 25017		1 or 2	1 or 2		1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		BS 25017		1 or 2	1 or 2		1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		BS 25017		1 or 2	1 or 2		1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		BS 25017		1 or 2	1 or 2		5/32" - 2.6 pcf	4.0mm - 42kg/m ³
		BS 25017		1 or 2	1 or 2		5/32" - 3.8 pcf	4.0mm - 61kg/m ³
		BS 25017		1 or 2	1 or 2		5/32" - 5.3 pcf	4.0mm - 85kg/m ³
		BS 25017		1 or 2	1 or 2		5/32" - 6.9 pcf	4.0mm - 110kg/m ³
		BS 25017		1 or 2	1 or 2		5/32" - 8.4 pcf	4.0mm - 134kg/m ³
		BS 25017		1 or 2	1 or 2		3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		BS 25017		1 or 2	1 or 2		3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		BS 25017		1 or 2	1 or 2		3/16" - 4.4 pcf	4.8mm - 70kg/m ³
		BS 25017		1 or 2	1 or 2		3/16" - 5.7 pcf	4.8mm - 91kg/m ³
		BS 25017		1 or 2	1 or 2		3/16" - 6.9 pcf	4.8mm - 110kg/m ³
		BS 25017		1 or 2	1 or 2		3/16" - 8.1 pcf	4.8mm - 130kg/m ³
		BS 25017		1 or 2	1 or 2		1/4" - 1.6 pcf	6.4mm - 26kg/m ³
		BS 25017		1 or 2	1 or 2		1/4" - 2.3 pcf	6.4mm - 37kg/m ³
		BS 25017		1 or 2	1 or 2		1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		BS 25017		1 or 2	1 or 2		1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		BS 25017		1 or 2	1 or 2		1/4" - 5.2 pcf	6.4mm - 83kg/m ³
		BS 25017		1 or 2	1 or 2		1/4" - 6.0 pcf	6.4mm - 96kg/m ³
		BS 25017		1 or 2	1 or 2		1/4" - 7.9 pcf	6.4mm - 126kg/m ³
		BS 25017		1 or 2	1 or 2		3/8" - 1.0 pcf	9.5mm - 16kg/m ³
		BS 25017		1 or 2	1 or 2		3/8" - 1.6 pcf	9.5mm - 26kg/m ³
		BS 25017		1 or 2	1 or 2		3/8" - 2.3 pcf	9.5mm - 37kg/m ³
		BS 25017		1 or 2	1 or 2		3/8" - 3.0 pcf	9.5mm - 48kg/m ³
		BS 25017		1 or 2	1 or 2		3/8" - 3.7 pcf	9.5mm - 59kg/m ³
		BS 25017		1 or 2	1 or 2		3/8" - 4.2 pcf	9.5mm - 67kg/m ³
BS 25017		1 or 2	1 or 2		3/8" - 5.4 pcf	9.5mm - 86kg/m ³		
BS 25017		1 or 2	1 or 2		3/8" - 6.5 pcf	9.5mm - 104kg/m ³		
Saab	PAA Aluminum Honeycomb - 5056 Alloy	STD 124230					1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		STD 124230					1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		STD 124230					1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		STD 124230					1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		STD 124230					5/32" - 3.8 pcf	4.0mm - 61kg/m ³
		STD 124230					1/4" - 3.4 pcf	6.4mm - 54kg/m ³
		STD 124230					1/4" - 4.3 pcf	6.4mm - 69kg/m ³
		STD 124230					1/4" - 5.2 pcf	6.4mm - 83kg/m ³
SAE	Dura-Core® Aluminum Honeycomb - 5052 and 5056 Alloy	AMS 4348, AMS 4349		5052 or 5056			1/8" - 3.1 pcf	3.2mm - 50kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			1/8" - 4.5 pcf	3.2mm - 72kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			1/8" - 6.1 pcf	3.2mm - 98kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			1/8" - 8.1 pcf	3.2mm - 130kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			5/32" - 2.6 pcf	4.0mm - 42kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			5/32" - 3.8 pcf	4.0mm - 61kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			5/32" - 5.3 pcf	4.0mm - 85kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			5/32" - 6.9 pcf	4.0mm - 110kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			5/32" - 8.4 pcf	4.0mm - 135kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			3/16" - 2.0 pcf	4.8mm - 32kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			3/16" - 3.1 pcf	4.8mm - 50kg/m ³
		AMS 4348, AMS 4349		5052 or 5056			3/16" - 4.4 pcf	4.8mm - 70kg/m ³

NOTES:
Class 1 = Non-Perforated Core
Class 2 = Perforated Core
Grade 1 = 5052 Aluminum Alloy
Grade 2 = 5056 Aluminum Alloy

NOTES:
 Available as Perforated and Non-Perforated Core
AMS 4348 is 5052 Aluminum Alloy Honeycomb
AMS 4349 is 5056 Aluminum Alloy Honeycomb
5052 and 5056 Aluminum Alloy is shown under CLASS category



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)		
SAE (Cont.)	Dura-Core® Aluminum Honeycomb - 5052 and 5056 Alloy	AMS 4348, AMS 4349		5052 or 5056			3/16" - 5.7 pcf	4.8mm - 91kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/16" - 6.9 pcf	4.8mm - 110kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/16" - 8.1 pcf	4.8mm - 130kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			1/4" - 1.6 pcf	6.4mm - 26kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			1/4" - 2.3 pcf	6.4mm - 37kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			1/4" - 3.4 pcf	6.4mm - 54kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			1/4" - 4.3 pcf	6.4mm - 69kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			1/4" - 5.2 pcf	6.4mm - 83kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			1/4" - 6.0 pcf	6.4mm - 96kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			1/4" - 7.9 pcf	6.4mm - 126kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 1.0 pcf	9.5mm - 16kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 1.6 pcf	9.5mm - 26kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 2.3 pcf	9.5mm - 37kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 3.0 pcf	9.5mm - 48kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 3.7 pcf	9.5mm - 59kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 4.2 pcf	9.5mm - 67kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 5.4 pcf	9.5mm - 86kg/m ³		
		AMS 4348, AMS 4349		5052 or 5056			3/8" - 6.5 pcf	9.5mm - 104kg/m ³		
		SAE	Dura-Core® or PAA Aluminum Honeycomb - 5052 and 5056 Alloy	AMS-C-7438	Type N or Type P	Class 1 or Class 2	B		1/8" - 3.1 pcf	3.2mm - 50kg/m ³
				AMS-C-7438	Type N or Type P	Class 1 or Class 2	B		1/8" - 4.5 pcf	3.2mm - 72kg/m ³
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/8" - 6.1 pcf	3.2mm - 98kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/8" - 8.1 pcf	3.2mm - 130kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/8" - 10.0 pcf	3.2mm - 160kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/8" - 12.0 pcf	3.2mm - 192kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		5/32" - 2.6 pcf	4.0mm - 42kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		5/32" - 3.8 pcf	4.0mm - 61kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		5/32" - 5.3 pcf	4.0mm - 85kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		5/32" - 6.9 pcf	4.0mm - 110kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/16" - 2.0 pcf	4.8mm - 32kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/16" - 3.1 pcf	4.8mm - 50kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/16" - 4.4 pcf	4.8mm - 70kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/16" - 5.7 pcf	4.8mm - 91kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/16" - 6.9 pcf	4.8mm - 110kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/16" - 8.1 pcf	4.8mm - 130kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/4" - 1.6 pcf	6.4mm - 26kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/4" - 2.3 pcf	6.4mm - 37kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/4" - 3.4 pcf	6.4mm - 54kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/4" - 4.3 pcf	6.4mm - 69kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/4" - 5.2 pcf	6.4mm - 83kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/4" - 6.0 pcf	6.4mm - 96kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		1/4" - 7.9 pcf	6.4mm - 126kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/8" - 1.0 pcf	9.5mm - 16kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/8" - 1.6 pcf	9.5mm - 26kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/8" - 2.3 pcf	9.5mm - 36kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/8" - 3.0 pcf	9.5mm - 48kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/8" - 3.7 pcf	9.5mm - 59kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/8" - 4.2 pcf	9.5mm - 67kg/m ³		
AMS-C-7438	Type N or Type P			Class 1 or Class 2	B		3/8" - 5.4 pcf	9.5mm - 87kg/m ³		
AMS-C-7438	Type N or Type P	Class 1 or Class 2	B		3/8" - 6.5 pcf	9.5mm - 104kg/m ³				
AMS-C-7438	Type N or Type P	Class 1 or Class 2	B		3/8" - 7.6 pcf	9.5mm - 122kg/m ³				
Safran	PAA Aluminum Honeycomb - 5052 and 5056 Alloy	HMRC 3001	HMDC3000-15	5056		PAA	1/8" - 6.1 pcf	3.2mm - 98kg/m ³		
		HMRC 3001	HMDC3003-20	5056		PAA	1/8" - 6.1 pcf	3.2mm - 98kg/m ³		
		HMRC 3001	HMDC3000-10	5056		PAA	1/8" - 8.1 pcf	3.2mm - 130kg/m ³		
		HMRC 3001	HMDC3003-10	5056		PAA	1/8" - 8.1 pcf	3.2mm - 130kg/m ³		

NOTES:
Class 1 = PAA, Phosphoric Acid Anodized - High Corrosion Resistance
Class 2 = DURA-CORE®, Standard Corrosion Resistance
Type N = Non-Perforated Core
Type P = Perforated Core



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)		
Safran (Cont.)	PAA Aluminum Honeycomb - 5052 and 5056 Alloy	HMRC 3007	HMDC3003-19	5052		PAA	1/8" - 8.1 pcf	3.2mm - 130kg/m ³		
		HMRC 3007	HMDC3003-21	5052		PAA	1/8" - 6.1 pcf	3.2mm - 98kg/m ³		
		HMRC 3005	HMDC3004-2	5052		PAA	3/32" - 22.1 pcf	2.4mm - 354kg/m ³		
		HMRC 3005	HMDC3002-2	5052		PAA	3/32" - 22.1 pcf	2.4mm - 354kg/m ³		
		HMRC 3001	HMDC3000-7	5056		PAA	3/16" - 4.4 pcf	4.8mm - 70kg/m ³		
		HMRC 3001	HMDC3003-7	5056		PAA	3/16" - 4.4 pcf	4.8mm - 70kg/m ³		
		HMRC 3007	HMDC3003-22	5052		PAA	3/16" - 4.4 pcf	4.8mm - 70kg/m ³		
		HMRC 3001	HMDC3000-8	5056		PAA	3/16" - 5.7 pcf	4.8mm - 91kg/m ³		
		HMRC 3001	HMDC3003-8	5056		PAA	3/16" - 5.7 pcf	4.8mm - 91kg/m ³		
		HMRC 3007	HMDC3003-17	5052		PAA	3/16" - 5.7 pcf	4.8mm - 91kg/m ³		
		HMRC 3007	HMDC3000-11	5052		PAA	3/16" - 8.1 pcf	4.8mm - 130kg/m ³		
		HMRC 3007	HMDC3003-18	5052		PAA	3/16" - 8.1 pcf	4.8mm - 130kg/m ³		
		HMRC 3001	HMDC3000-5	5056		PAA	1/4" - 6.0 pcf	6.4mm - 96kg/m ³		
		HMRC 3001	HMDC3003-5	5056		PAA	1/4" - 6.0 pcf	6.4mm - 96kg/m ³		
		HMRC 3007	HMDC3003-15	5052		PAA	1/4" - 6.0 pcf	6.4mm - 96kg/m ³		
		HMRC 3001	HMDC3000-6	5056		PAA	1/4" - 7.9 pcf	6.4mm - 127kg/m ³		
		HMRC 3001	HMDC3003-6	5056		PAA	1/4" - 7.9 pcf	6.4mm - 127kg/m ³		
		HMRC 3007	HMDC3003-16	5052		PAA	1/4" - 7.9 pcf	6.4mm - 127kg/m ³		
		HMRC 3001	HMDC3000 - 1	5056		PAA	3/8" - 3.0 pcf	9.5mm - 48kg/m ³		
		HMRC 3001	HMDC3003-1	5056		PAA	3/8" - 3.0 pcf	9.5mm - 48kg/m ³		
		HMRC 3007	HMDC3003-11	5052		PAA	3/8" - 3.0 pcf	9.5mm - 48kg/m ³		
		HMRC 3001	HMDC3000-2	5056		PAA	3/8" - 4.2 pcf	9.5mm - 67kg/m ³		
		HMRC 3001	HMDC3003-2	5056		PAA	3/8" - 4.2 pcf	9.5mm - 67kg/m ³		
		HMRC 3007	HMDC3003-12	5052		PAA	3/8" - 4.2 pcf	9.5mm - 67kg/m ³		
		HMRC 3001	HMDC3000-3	5056		PAA	3/8" - 5.4 pcf	9.5mm - 86kg/m ³		
		HMRC 3001	HMDC3003-3	5056		PAA	3/8" - 5.4 pcf	9.5mm - 86kg/m ³		
		HMRC 3007	HMDC3003-13	5052		PAA	3/8" - 5.4 pcf	9.5mm - 86kg/m ³		
		HMRC 3001	HMDC3000-4	5056		PAA	3/8" - 6.5 pcf	9.5mm - 104kg/m ³		
		HMRC 3001	HMDC3003-4	5056		PAA	3/8" - 6.5 pcf	9.5mm - 104kg/m ³		
		HMRC 3007	HMDC3000-14	5052		PAA	3/8" - 6.5 pcf	9.5mm - 105kg/m ³		
		HMRC 3007	HMDC3003-14	5052		PAA	3/8" - 6.5 pcf	9.5mm - 105kg/m ³		
		HMRC 3003	HMDC3006-1, over-expanded	5056		PAA	3/16" - 4.4pcf	4.8mm - 70kg/m ³		
		HMRC 3003	HMDC3001-1, over-expanded	5056		PAA	3/16" - 4.4pcf	4.8mm - 70kg/m ³		
		HMRC 3003	HMDC3006-3, over-expanded	5052		PAA	3/16" - 8.1pcf	4.8mm - 130kg/m ³		
		HMRC 3003	HMDC3001-3, over-expanded	5052		PAA	3/16" - 8.1pcf	4.8mm - 130kg/m ³		
		HMRC 3003	HMDC3006-4, over-expanded	5052		PAA	3/16" - 4.4pcf	4.8mm - 70kg/m ³		
		HMRC 3003	HMDC3006-5, maxi-expanded	5056		PAA	3/16" - 4.4pcf	4.8mm - 70kg/m ³		
		HMRC 3003	HMDC3001-5, maxi-expanded	5056		PAA	3/16" - 4.4pcf	4.8mm - 70kg/m ³		
		HMRC 3003	HMDC3006-7, maxi-expanded	5052		PAA	3/16" - 8.1pcf	4.8mm - 130kg/m ³		
		HMRC 3003	HMDC3001-7, maxi-expanded	5052		PAA	3/16" - 8.1pcf	4.8mm - 130kg/m ³		
		HMRC 3003	HMDC3006-8, maxi-expanded	5052		PAA	3/16" - 4.4pcf	4.8mm - 70kg/m ³		
		Sonaca	Dura-Core® Aluminum Honeycomb - 5052 and 5056 Alloy	SMS1003		5052		DURA-CORE®	1/8" - 6.1 pcf	3.2mm - 96kg/m ³
				SMS1005		5056		DURA-CORE®	5/32" - 2.6 pcf	4.0mm - 42kg/m ³
				SMS1003/SMS1005		5052 or 5056		DURA-CORE®	5/32" - 3.8 pcf	4.0mm - 61kg/m ³
				SMS1003		5052		DURA-CORE®	5/32" - 5.3 pcf	4.0mm - 85kg/m ³
SMS1003				5052		DURA-CORE®	3/16" - 3.1 pcf	4.8mm - 50kg/m ³		
SMS1003				5052		DURA-CORE®	1/4" - 4.3 pcf	6.4mm - 69kg/m ³		
11014180-1	NEX			5052		DURA-CORE®	1/8" - 3.1 pcf	3.2mm - 50kg/m ³		
10903820-5				5052		DURA-CORE®	1/8" - 4.5 pcf	3.2mm - 72kg/m ³		
10903820-5				5052		DURA-CORE®	1/8" - 6.1 pcf	3.2mm - 98kg/m ³		
11014180-1	NEX			5052		DURA-CORE®	1/8" - 6.1 pcf	3.2mm - 98kg/m ³		
10903820-5				5052		DURA-CORE®	3/16" - 2.0 pcf	4.8mm - 32kg/m ³		
11014180-1	NEX			5052		DURA-CORE®	3/16" - 2.0 pcf	4.8mm - 32kg/m ³		
10903820-5				5056		DURA-CORE®	1/4" - 1.6 pcf	6.4mm - 26kg/m ³		

NOTES:
HRMC 3001 = PAA Phosphoric Acid Anodized, 5056 Alloy Core
HRMC 3005 Corrugated Higrd® = PAA Phosphoric Acid Anodized, 5052 Alloy Core
HRMC 3007 = PAA, 5052 Alloy Core

NOTES:
SMS 1003 = 5052 Aluminum Alloy
SMS 1005 = 5056 Aluminum Alloy
Type NEX = Unexpanded Slices



Original Equipment Manufacturer	Product	Specification	Type	Class	Grade	Form	Cell Size-Density (English)	Cell Size-Density (Metric)
Sonaca (Cont.)	Dura-Core® Aluminum	11014180-1	NEX	5056		DURA-CORE®	1/4" - 1.6 pcf	6.4mm - 26kg/m ³
	Honeycomb - 5052 and 5056 Alloy	10903820-5		5056		PAA	3/8" - 1.0 pcf	9.5mm - 16kg/m ³
		11014180-1	NEX	5056		PAA	3/8" - 1.0 pcf	9.5mm - 16kg/m ³

Dura-Core® and PAA-Core® are registered trademarks of The Gill Corporation.

HIGH PERFORMANCE COMPOSITE PRODUCTS SINCE 1945

The Gill Corporation
 International Headquarters
 4056 Easy Street
 El Monte, CA 91731 USA
 Phone: +1 626-443-4022
 Email: info@thegillcorp.com

The Gill Corporation-Maryland
 Lakeside Business Park
 1502 Quarry Drive
 Edgewood, MD 21040 USA
 Phone: +1 410-676-7100
 Email: sales@thegillcorp.com

The Gill Corporation-France
 Route de l'Aviation
 7, Allee Etchecopar
 64600 Anglet France
 Phone: +33 0 5 59 41 25 25
 Email: sales@thegillcorp.com

The Gill Corporation-Europe
 23 Enterprise Road
 Bangor, Co-Down, BT19 7TA
 Northern Ireland, United Kingdom
 Phone: +44 0 2891 470073
 Email: sales@thegillcorp.com