

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/13/2015 Revision date: 04/07/2022 Supersedes: 09/30/2002

SECTION 1: Identification of the substance/mixture and of the company/undertaking

I.1. Product identifier

Product form : Mixture

Product name : Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to

a Nomex® Aramid Honeycomb Core

Other means of identification : Gillfab® 4422 Panel

Gillfab® 4122A Panel Gillfab® 4122B Panel Gillfab® 4122C Panel Gillfab® 4122S Panel

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Versatile Panels typically used for aircraft interior

1.3. Details of the supplier of the safety data sheet

The Gill Corporation 4056 Easy Street El Monte, CA 91731 www.thegillcorp.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Carc. 1B H350 STOT SE 1 H370

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H350 - May cause cancer (Dermal, Inhalation, oral)

H370 - Causes damage to organs

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust

P264 - Wash hands, forearms and face thoroughly after handling P270 - Do not eat, drink or smoke when using this product

P280 - Wear face protection, protective gloves P307 + P311 - If exposed: Call a poison center/doctor

P308 + P313 - If exposed or concerned: Get medical advice/attention P321 - Specific treatment (see Section four (4) of this document on this label)

P405 - Store locked up

P501 - Dispose of contents/container to comply with local/regional/national/international

regulations

2.3. Other hazards

Other hazards not contributing to the classification

: As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting. Other constituents in this product are considered nuisance particles or dust. Exposure to dusts or powders may cause mechanical irritation of the respiratory system, eyes, and skin.

F201 - 6/18 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Fiberglass	(CAS No) 65997-17-3	15 - 60	Carc. 1B, H350
Co-cured phenolic resin/synthetic elastomer(containing Methanol, Phenol, Formaldehyde)	(CAS No) Proprietary	35 - 55	Carc. 2, H351 STOT SE 1, H370
Nomex Paper	(CAS No) 25765-47-3	1 - 35	Not classified
Polyvinyl/fluoride polymer containing less than 0.025% nickel antimony titanium yellow pigment as nickel compounds	(CAS No) 24981-14-4	0 - 3	Carc. 1A, H350
Cured Epoxy Adhesive	(CAS No) Proprietary	0 - 2	Comb. Dust, H232
Dibromoneopentyl glycol	(CAS No) 3296-90-0	0 - 2.5	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 2, H401 Muta. 2, H341

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call 911 or emergency medical service. Move victim to fresh air. Keep victim warm and quiet.

Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If exposed: Remove person to fresh air, If person is not breathing, provide artificial respiration. If necessary, provide additional

fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.

First-aid measures after skin contact : In case of burns, immediately cool affected skin for as long as possible with cold water. Do not

remove clothing if adhering to skin.

First-aid measures after eye contact : Immediately flush with large amounts of water, holding eyelids open, for at least 20 minutes.

Repeat if necessary. Remove contact lenses, if present and easy to do. Seek medical

assistance if irritation persists.

First-aid measures after ingestion : Not an anticipated route of entry.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.

Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation.

Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.

Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially

severe, can result from eye contact with this material.

Symptoms/injuries after ingestion : May cause toxic effects if inhaled or ingested/swallowed.

Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the

underlying condition if exposed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Any. Use media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Product will not burn.

F201 - 6/18 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard : Can decompose in a fire emitting toxic fumes and gases of carbon dioxide, carbon monoxide,

methane, formaldehyde, phenol, hydrogen cyanide, hydrogen bromide, hydrogen chloride, oxides of nitrogen, small amounts of aromatic and aliphatic hydrocarbons; other toxic and

irritating gases can be produced depending on condition of combustion.

5.3. Advice for firefighters

Firefighting instructions : Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Firefighters should wear a NIOSH approved full-face piece self-contained breathing apparatus

(SCBA) operated in positive pressure mode and full turnout or bunker gear.

Other information : If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all

directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas.

Avoid breathing dust.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear positive pressure self-contained breathing apparatus (SCBA). Wear protective closing, a

properly fitted, air-purifying or air-fed respirator if a risk assessment indicates this is necessary,

chemical-resistant gloves, safety glasses.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

6.3. Methods and material for containment and cleaning up

For containment : Do not walk through any dust resulting from damage to product. Prevent entry into waterways,

sewers, basements or confined areas.

Methods for cleaning up : Pick up product and return to original packaging if reusable. If not reusable, place in

appropriate containers for disposal. Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Use methods to minimize dust. Do not breathe dust. DO NOT

use compressed air or dry sweeping to remove dust from work area. Use a vacuum with adequate filtration system to remove dusts. If an appropriate vacuum is unavailable, only wetclean-up methods should be used (i.e. misting). Moisture should be added as necessary to

reduce exposure to airborne respirable dust.

Hygiene measures : Practice good housekeeping. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in tightly closed containers out of contact with the elements.

Incompatible products : Strong acids. Reducing agents.

Packaging materials : Place carefully in dry, water-tight containers. Seal containers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core		
ACGIH	Not applicable	
OSHA	Not applicable	

F201 - 6/18 EN (English US) 3/8

Safety Data Sheet

Fiberglass (65997-17-3)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Not applicable	Not applicable		
OSHA PEL (TWA) (mg/m³)	3 fibers/cm³ (fibers with diameter ≤ 3.5 μm & length ≥ 10 μm); 5 mg/m3 TWA (total fibrous glass)		
Cured Epoxy Adhesive (Proprietary) Particulates Not Otherwise Regulated			
Not applicable	Not applicable		
Not applicable	Not applicable		
Nomex Paper (25765-47-3)			
Not applicable	Not applicable		
Not applicable			
	OSHA PEL (TWA) (mg/m³) ve (Proprietary) Particulates Not Otherwise Regulates Not applicable Not applicable 47-3) Not applicable		

Co-cured phenolic resin/synthetic elastomer (containing methanol, Phenol, Formaldenyde) (Proprietary)		
ACGIH	Not applicable	
OSHA	Not applicable	

Consumed when all a manimum with a time and a manimum Mathemal, Dhowal, Formal debude \(\text{(Proprietors)}\)

Polyvinyl/fluoride polymer containing less than 0.025% nickel antimony titanium yellow pigment as nickel compounds (24981-14-4)		
ACGIH	Not applicable	
OSHA	Not applicable	

Flame Retardant (Proprietary)		
ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ Respirable
OSHA	OSHA PEL (TWA) (mg/m³)	5mg/m³ Respirable

Particulates Not Otherwise Regulated (Total Dust)		
ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ Respirable; 10 mg/m³ Total dust
OSHA	OSHA PEL (TWA) (mg/m³)	5mg/m³ Respirable; 15 mg/m³ Total dust

8.2. Exposure controls

Eye protection

Skin and body protection

Respiratory protection

Appropriate engineering controls	: General ventilation. Local exhaust and enclosed processes may be necessary for processes
	which generate large quantities of airborne dust.

Personal protective equipment : An Appropriate apron or other body covering, see above, is recommended where there is a possibility of regular work clothing becoming contaminated with the product. All soiled or dirty

possibility of regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned before reuse.

: Where eye contact is possible with particulate matter, safety glasses with side shields are recommended.

: Use insulated, impervious plastic or neoprene-coated canvas gloves and protective gear (apron, face shield, etc.) to protect hands and other skin areas.

Respiratory protection is not normally required. If appreciable dusts and/or particulate matter are generated during handling or processing, the operation should be evaluated by a professional industrial hygienist to determine the need for respiratory protection. If respiratory protection is deemed necessary, use, as a minimum, a respirator with NIOSH approvals for particulate matter. All provisions of OSHA's Respiratory Protection Standard (29 CFR 1910.134) should be followed. If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Sandwich panel.

Color : Tan; white

Odor : Sweet

Odor threshold : No data available pH : No data available

F201 - 6/18 EN (English US) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1) No data available Melting point No data available Freezing point No data available Boiling point No data available Flash point No data available No data available Auto-ignition temperature Decomposition temperature No data available Flammability (solid, gas) No data available Vapor pressure No data available Relative vapor density at 20 °C No data available Relative density 0.1-1.1g/cc Solubility Unknown. Log Pow No data available Log Kow No data available No data available Viscosity, kinematic No data available Viscosity, dynamic Explosive properties No data available Oxidizing properties No data available **Explosive limits** No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Product is stable. Hazardous polymerization will not occur.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong oxidizing agents, strong acids and bases, especially oxalic and hydrofluoric acid and acyl halides

10.6. Hazardous decomposition products

Decomposition and combustion products may be toxic. Can decompose in a fire emitting toxic fumes and gases of carbon dioxide, carbon monoxide, methane, formaldehyde, phenol, hydrogen cyanide, hydrogen bromide, hydrogen chloride, oxides of nitrogen, small amounts of aromatic and aliphatic hydrocarbons; other toxic and irritating gases can be produced depending on condition of combustion.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Flame Retardant (Proprietary)	
ATE US (oral)	500.000 mg/kg body weight
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Dermal, Inhalation, oral).
Fiberglass (65997-17-3)	
IARC group	3 - Not classifiable

F201 - 6/18 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Fiberglass (65997-17-3)	
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Polyvinyl/fluoride polymer containing less than 0.025% nickel antimony titanium yellow pigment as nickel compounds (24981-14-4)		
IARC group	1 - Carcinogenic to humans	
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens	

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Causes damage to organs.

Specific target organ toxicity (repeated

exposure)

Not classified

Aspiration hazard : Not classified

Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below

apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.

Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation.

Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.

Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially

severe, can result from eye contact with this material.

Symptoms/injuries after ingestion : May cause toxic effects if inhaled or ingested/swallowed.

Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by

excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the

underlying condition if exposed.

12.1. Toxicity

Ecology - general : This product has no known eco-toxicological effects.

12.2. Persistence and degradability

No additional information available

12.3. Bio accumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : If material as supplied becomes a waste, incinerate or landfill in accordance with local, state, and federal laws and regulations. Incinerate only if incinerator is operated at high temperature

and is capable of scrubbing out acidic combustion products. Contact your local or state environmental agency for specific rules.

· Empty containers will contain product residues. Observe

: Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers to be used for any purpose except to store and

ship original product.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Additional information

Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

F201 - 6/18 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory except for:

Cured Epoxy Adhesive	CAS No Proprietary	C<=2.00%
Nomex Paper	CAS No 25765-47-3	C>=1.00%; C<=35.00%
Co-cured phenolic resin/synthetic elastomer(containing Methanol, Phenol, Formaldehyde)	CAS No Proprietary	C>=35.00% ; C<=55.00%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de Minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Co-cured phenolic resin/synthetic elastomer (containing Methanol, Phenol, Formaldehyde) (Proprietary)		
EPA TSCA Regulatory Flag	All components of this product are listed on the TSCA inventory.	

15.2. International regulations

CANADA

No additional information available

Co-cured phenolic resin/synthetic elastomer (containing Methanol, Phenol, Formaldehyde) (Proprietary)		
WHMIS Classification	Class B Division 2 - Flammable Liquid	
	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Fiberglass (65997-17-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Co-cured phenolic resin/synthetic elastomer (containing Methanol, Phenol, Formaldehyde) (Proprietary)					
U.S Calif Proposition Carcinoger	1 65 -	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes		No	No	No	

F201 - 6/18 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flame Retardant (Proprietary)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

SECTION 16: Other information

Revision date : 09/17/2015

Data sources : ChemADVISOR, Inc.[https://www.chemadvisor.com]. ChemIDplus

 $[http://chem.sis.nlm.nih.gov/chemidplus/rn/116094-23-6]. \ GESTIS \ DNEL \ Database \ [http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates\$fn=default.htm\$vid=dneleng:ddb$

eng\$3.0/].

Full text of H-phrases:

ext of Fi-prilases.	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Carc. 1A Carcinogenicity Category 1A	
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H232	May form combustible dust concentrations in air
H302	Harmful if swallowed
H350	May cause cancer
H351	Suspected of causing cancer
H370	Causes damage to organs
H401	Toxic to aquatic life

NFPA health hazard : 2 - Intense or continued exposure could cause temporary


incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 3 - Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 - Minimal Hazard
Physical : 0 - Minimal Hazard

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

F201 - 6/18 EN (English US) 8/8