



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Hybrid Laminate Composed of Aluminum Facings Bonded to Fiberglass/Epoxy Laminate Core
 Other means of identification : Gillfab® 5433F

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cargo compartment flooring panel

1.3. Details of the supplier of the safety data sheet

The Gill Corporation
 4056 Easy Street
 El Monte, CA 91731
 (626) 443-4022
www.thegillcorp.com

1.4. Emergency telephone number

Emergency number : THE GILL CORPORATION: 1-626-443-4022 CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Irrit. 2 H315
 Eye Irrit. 2A H319
 Skin Sens. 1 H317
 Carc. 1B H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H350 - May cause cancer (Dermal, Inhalation, oral)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P261 - Avoid breathing mist, dust, fume
 P264 - Wash hands, forearms and face thoroughly after handling
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P280 - Wear face protection, protective gloves
 P302 + P352 - If on skin: Wash with plenty of water
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P308 + P313 - If exposed or concerned: Get medical advice/attention
 P321 - Specific treatment (see Section four (4) of this document on this label)
 P332+P313 - If skin irritation occurs: Get medical advice/attention
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P362 - Take off contaminated clothing and wash before reuse
 P362+P364 - Take off contaminated clothing and wash it before reuse
 P405 - Store locked up
 P501 - Dispose of contents/container to comply with local/regional/national/international regulations

Hybrid Laminate Composed of Aluminum Facings Bonded to Fiberglass/Epoxy Laminate Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards

Other hazards not contributing to the classification : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or pulverizing. This product contains strontium chromate (Gillfab 5433A only) at < 0.4%. Strontium chromate contains 25.5 weight percent hexavalent chromium, which is listed as a carcinogen by NTP, IARC, and OSHA. Prolonged exposure may cause blood, gastrointestinal, nervous, and reproductive effects. Protective equipment should be used to minimize contact with this material, but it is not expected to present a significant hazard under normal handling.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Aluminum	(CAS No) 7429-90-5	60 - 80	Not classified
Fiberglass	(CAS No) 65997-17-3	19 - 30	Carc. 1B, H350
Epoxy Resin	Proprietary	5 - 16	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Get medical aid immediately. Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately flush with large amounts of water, holding eyelids open, for at least 20 minutes. Repeat if necessary. Remove contact lenses, if present and easy to do. Seek medical assistance if irritation persists.

First-aid measures after ingestion : Not expected to be an important route of entry into the body. If large amounts of particulate matter are ingested, it may cause gastrointestinal distress. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.

Symptoms/injuries after inhalation : Inhalation of aluminum powder may cause lung effects. Inhalation of metallic dust may be hazardous. Dust and fumes produced during processing should be treated as a dust hazard. Repeated and prolonged inhalation of aluminum powder may cause serious lung disorders... This product contains aluminum, which can cause pulmonary fibrosis and lung damage if inhaled as a fine powder, and is complicated by silica and iron oxide dust. Aluminum may also be implicated in Alzheimer's disease.

Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin. Repeated prolonged exposure may cause slow-healing skin lesions and allergic reactions.

Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes.

Symptoms/injuries after ingestion : Not expected to be an important route of entry into the body. Ingestion of large quantities of the product may cause gastric discomfort or distress.

Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Hybrid Laminate Composed of Aluminum Facings Bonded to Fiberglass/Epoxy Laminate Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : As packaged: Any. Use media appropriate for surrounding fire.
If dust/powder fire is generated: Use a Class D fire extinguisher.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Can decompose in a fire emitting toxic fumes and gases of carbon dioxide, carbon monoxide, oxides of nitrogen, metal oxides; other toxic and irritating gases can be produced depending on condition of combustion.

Explosion hazard : Aluminum dust is readily ignitable and explosive when suspended in air. In case of fire: Use extreme care to prevent dust cloud formation.

5.3. Advice for firefighters

Firefighting instructions : Use DRY sand, graphite powder, dry sodium chloride based extinguishers, G-1® or Met-L-X® powder.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Firefighters should wear a NIOSH approved full-face piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear.

Special protective equipment for fire fighters : Wear full bunker gear including a positive pressure self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : May react violently or explosively on contact with water. Dousing metallic fires with water will generate hydrogen gas, an extremely dangerous explosion hazard, particularly if fire is in a confined environment (i.e., building, cargo hold, etc.). Containers may explode when heated. May re-ignite after fire is extinguished.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

6.3. Methods and material for containment and cleaning up

For containment : Move containers from fire area if you can do it without risk. DO NOT USE WATER, FOAM OR CO₂. Confining and smothering metal fires is preferable rather than applying water. If impossible to extinguish, protect surroundings and allow fire to burn it out.

Methods for cleaning up : HEPA Vacuum or wet methods and place in a disposal container.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Good housekeeping and engineering practices should be employed to prevent the generation and accumulation of dusts. DO NOT USE WATER for spill clean-up. Avoid dusting of powder to the greatest extent. Sweep spilled powder with natural bristle broom (push type recommended). Pick up material with a non-sparkling shovel. After complete clean up by sweeping, area may be washed down with copious quantities of water, if necessary.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in tightly closed containers out of contact with the elements.

Incompatible products : Strong acids. Reducing agents.

Packaging materials : Place carefully in dry, water-tight containers. Seal containers.

7.3. Specific end use(s)

Use of the substance/mixture : Cargo compartment flooring panel

Hybrid Laminate Composed of Aluminum Facings Bonded to Fiberglass/Epoxy Laminate Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aluminum (7429-90-5)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (respirable fraction)
ACGIH	Remark (ACGIH)	Pneumoconiosis; LRT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (respirable particulate)
OSHA	Remark (US OSHA)	15 mg/m ³ (total dust)

Epoxy Resin (25068-38-6)	
ACGIH	Not applicable
OSHA	Not applicable

Fiberglass (65997-17-3)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls	: General ventilation. Local exhaust and enclosed processes may be necessary for processes which generate large quantities of airborne dust.
Personal protective equipment	: An Appropriate apron or other body covering, see above, is recommended where there is a possibility of regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned before reuse.
Eye protection	: Where eye contact is possible with particulate matter, safety glasses with side shields are recommended.
Skin and body protection	: Use insulated, impervious plastic or neoprene-coated canvas gloves and protective gear (apron, face shield, etc.) to protect hands and other skin areas.
Respiratory protection	: If dusts or particulates are generated during handling or processing and exposures may exceed the limits cited above, use, as a minimum, a NIOSH approved ½ face piece respirator with cartridges approved for particulate matter with an exposure limit of not less than 0.05 mg/M3.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Sandwich panel.
Color	: Metallic; Grayish in Color
Odor	: None.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 2.0-2.5g/cc
Solubility	: Unknown.
Log Pow	: No data available
Log Kow	: No data available

Hybrid Laminate Composed of Aluminum Facings Bonded to Fiberglass/Epoxy Laminate Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Product is stable. Hazardous polymerization will not occur.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Aluminum dust may generate hydrogen and heat when exposed to water. Water/aluminum powder mixture may be especially hazardous when confined and may react violently with strong oxidizers and many halogenated hydrocarbons.

10.5. Incompatible materials

Strong oxidizing agents, strong acids and bases, especially oxalic and hydrofluoric acid and acyl halides.

10.6. Hazardous decomposition products

Decomposition and combustion products may be toxic. Can decompose in a fire emitting toxic fumes and gases of carbon dioxide, carbon monoxide, metal oxides; oxides of nitrogen and other toxic and irritating gases can be produced depending on condition of combustion.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Dermal, Inhalation, oral).

Fiberglass (65997-17-3)

IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries	: As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.
Symptoms/injuries after inhalation	: Inhalation of aluminum powder may cause lung effects. Inhalation of metallic dust may be hazardous. Dust and fumes produced during processing should be treated as a dust hazard. Repeated and prolonged inhalation of aluminum powder may cause serious lung disorders.. This product contains aluminum, which can cause pulmonary fibrosis and lung damage if inhaled as a fine powder, and is complicated by silica and iron oxide dust. Aluminum may also be implicated in Alzheimer's disease.
Symptoms/injuries after skin contact	: Dusts and particulate matter may cause irritation of the skin. Repeated prolonged exposure may cause slow-healing skin lesions and allergic reactions.
Symptoms/injuries after eye contact	: Dusts and particulate matter may cause irritation of the eyes.
Symptoms/injuries after ingestion	: Not expected to be an important route of entry into the body. Ingestion of large quantities of the product may cause gastric discomfort or distress.

Hybrid Laminate Composed of Aluminum Facings Bonded to Fiberglass/Epoxy Laminate Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bio accumulative potential

Not expected to be acutely or chronically ecotoxic.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers to be used for any purpose except to store and ship original product.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Sandwich Panels Composed of Aluminum Skins Bonded To Glass/Epoxy Core

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de Minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Aluminum (7429-90-5)

Listed on United States SARA Section 313

Hybrid Laminate Composed of Aluminum Facings Bonded to Fiberglass/Epoxy Laminate Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Aluminum (7429-90-5)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

SECTION 16: Other information

Full text of H-phrases:

Carc. 1B	Carcinogenicity Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H350	May cause cancer

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 1 - Slight Hazard - Irritation or minor reversible injury possible

Flammability : 0 - Minimal Hazard

Physical : 0 - Minimal Hazard

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product