



THE GILL CORPORATION

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register /

Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/31/2015 Revision date: 07/24/2024 Supersedes: 11/07/2008

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core
Other means of identification : Gillfloor® 4518

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : The cargo liner is designed for use in the cargo compartment, bulkhead facings, and blowout panels for aircraft. Also used as backing material for non-textile floor mats in wet areas of cabin interior.

1.3. Details of the supplier of the safety data sheet

The Gill Corporation
4056 Easy Street
El Monte, CA 91731
(626) 443-4022
www.thegillcorp.com

1.4. Emergency telephone number

Emergency number : THE GILL CORPORATION: 1-626-443-4022 CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Carc. 1B H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H350 - May cause cancer
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P280 - Wear face protection, protective gloves
P308 + P313 - If exposed or concerned: Get medical advice/attention
P405 - Store locked up
P501 - Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

Other hazards not contributing to the classification : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting. Other constituents in this product are considered nuisance particles or dust. Exposure to dusts or powders may cause mechanical irritation of the respiratory system, eyes, and skin. This product contains trace amounts of Antimony compounds.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Fiberglass	(CAS No) 65997-17-3	1 - 60	Carc. 1B, H350
Kevlar Paper	(CAS No) 26125-61-1	2 - 30	Not classified
Co-Cured Epoxy Resin/Synthetic elastomer	(CAS No) Proprietary	8 - 30	Eye Dam. 1, H318 STOT SE 3, H335
Cured Epoxy Adhesive	(CAS No) Proprietary	5 - 20	Comb. Dust, H232
Antimony Pentoxide	(CAS No) 1314-60-9	3 - 8	Not classified

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call 911 or emergency medical service. Move victim to fresh air. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If exposed: Remove person to fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.
- First-aid measures after skin contact : In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- First-aid measures after eye contact : Immediately flush with large amounts of water, holding eyelids open, for at least 20 minutes. Repeat if necessary. Remove contact lenses, if present and easy to do. Seek medical assistance if irritation persists.
- First-aid measures after ingestion : Not an anticipated route of entry.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or pulverizing.
- Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation.
- Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.
- Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
- Symptoms/injuries after ingestion : May cause toxic effects if inhaled or ingested/swallowed.
- Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Any. Use media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Product will not burn.
- Explosion hazard : Vapor explosion and poison hazard indoors, outdoors or in sewers. Containers may explode when heated.

5.3. Advice for firefighters

- Firefighting instructions : Evacuate area.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Firefighters should wear a NIOSH approved full-face piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear.

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Avoid breathing dust.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear positive pressure self-contained breathing apparatus (SCBA). Wear protective clothing, a properly fitted, air-purifying or air-fed respirator if a risk assessment indicates this is necessary, chemical-resistant gloves, safety glasses.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

6.3. Methods and material for containment and cleaning up

For containment : Do not walk through any dust resulting from damage to product. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up : Pick up product and return to original packaging if reusable. If not reusable, place in appropriate containers for disposal. Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Use methods to minimize dust. Do not breathe dust. DO NOT use compressed air or dry sweeping to remove dust from work area. Use a vacuum with adequate filtration system to remove dusts. If an appropriate vacuum is unavailable, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable dust.

Hygiene measures : Practice good housekeeping. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in tightly closed containers out of contact with the elements.
Incompatible products : Strong acids. Reducing agents.
Storage temperature : 10 °C (For maximum storage life. Store at temperature below 50°F)
Packaging materials : Place carefully in dry, water-tight containers. Seal containers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Kevlar Aramid Honeycomb Core		
ACGIH	Not applicable	
OSHA	Not applicable	
Fiberglass (65997-17-3)		
ACGIH	Not applicable	
OSHA	OSHA PEL (TWA) (mg/m³)	3 fibers/cm³ (fibers with diameter ≤ 3.5 µm & length ≥ 10 µm); 5 mg/m3 TWA (total fibrous glass)

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Antimony Pentoxide (1314-60-9)		
ACGIH	TLV	0.5 mg/m³ resp dust
OSHA	OSHA PEL (TWA) (mg/m³)	0.5 mg/m³ resp dust
Co-Cured Epoxy Resin/Synthetic elastomer (Proprietary) Particulates Not Otherwise Regulated		
ACGIH	Not applicable	
OSHA	Not applicable	
Cured Epoxy Adhesive (Proprietary) Particulates Not Otherwise Regulated		
ACGIH	Not applicable	
OSHA	Not applicable	
Kevlar Paper (26125-61-1)		
ACGIH	Not applicable	
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ total dust; Resp Dust 5 mg/m³
Particulates Not Otherwise Regulated (Total Dust)		
ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ Respirable; 10 mg/m³ Total dust
OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ Respirable; 15 mg/m³ Total dust

8.2. Exposure controls

Appropriate engineering controls	: General ventilation. Local exhaust and enclosed processes may be necessary for processes which generate large quantities of airborne dust.
Personal protective equipment	: An Appropriate apron or other body covering, see above, is recommended where there is a possibility of regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned before reuse.
Eye protection	: Where eye contact is possible with particulate matter, safety glasses with side shields are recommended.
Skin and body protection	: Use insulated, impervious plastic or neoprene-coated canvas gloves and protective gear (apron, face shield, etc.) to protect hands and other skin areas.
Respiratory protection	: Respiratory protection is not normally required. If appreciable dusts and/or particulate matter are generated during handling or processing, the operation should be evaluated by a professional industrial hygienist to determine the need for respiratory protection. If respiratory protection is deemed necessary, use, as a minimum, a respirator with NIOSH approvals for particulate matter. All provisions of OSHA's Respiratory Protection Standard (29 CFR 1910.134) should be followed. If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Sandwich panel.
Color	: Off white
Odor	: Slight characteristic odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.2-0.5 g/cc
Solubility	: Unknown.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Product is stable. Hazardous polymerization will not occur.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong oxidizing agents, strong acids and bases, especially oxalic and hydrofluoric acid and acyl halides.

10.6. Hazardous decomposition products

Decomposition and combustion products may be toxic. Can decompose in a fire emitting toxic fumes and gases of carbon dioxide, carbon monoxide, hydrogen cyanide, antimony oxides, hydrogen bromide; oxides of nitrogen and other toxic and irritating gases can be produced depending on condition of combustion.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Dermal, Inhalation, oral).

Fiberglass (65997-17-3)

IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries	: As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or pulverizing.
Symptoms/injuries after inhalation	: Inhalation of dust may result in itching and upper respiratory tract irritation.
Symptoms/injuries after skin contact	: Dusts and particulate matter may cause irritation of the skin.
Symptoms/injuries after eye contact	: Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
Symptoms/injuries after ingestion	: May cause toxic effects if inhaled or ingested/swallowed.
Chronic symptoms	: Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This product has no known eco-toxicological effects.

12.2. Persistence and degradability

No additional information available

12.3. Bio accumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: If material as supplied becomes a waste, incinerate or landfill in accordance with local, state, and federal laws and regulations. Incinerate only if incinerator is operated at high temperature and is capable of scrubbing out acidic combustion products. Contact your local or state environmental agency for specific rules.
Additional information	: Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers to be used for any purpose except to store and ship original product.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Kevlar Aramid Honeycomb Core

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory except for:

Cured Epoxy Adhesive	CAS No Proprietary	C>=5.00% ; C<=20.00%
Cured Phenolic Resin(s)	CAS No Proprietary	C>=5.00% ; C<=45.00%
Kevlar Paper	CAS No 26125-61-1	C>=2.00% ; C<=30.00%
Co-Cured Epoxy Resin/Synthetic elastomer	CAS No	C>=8.00% ; C<=30.00%

Antimony Pentoxide (1314-60-9)

Listed on United States SARA Section 313

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Fiberglass (65997-17-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Antimony pentoxide (as Antimony) (1314-60-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Data sources

: ChemADVISOR, Inc.[<https://www.chemadvisor.com>]. ChemIDplus [<http://chem.sis.nlm.nih.gov/chemidplus/rn/116094-23-6>]. GESTIS DNEL Database [[http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates\\$fn=default.htm\\$vid=dneleng:ddbeng\\$3.0/](http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates$fn=default.htm$vid=dneleng:ddbeng$3.0/)].

Full text of H-phrases:

Carc. 1B	Carcinogenicity Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H318	Causes serious eye damage
H335	May cause respiratory irritation
H350	May cause cancer

Sandwich Panels Composed of Fiberglass Reinforced Epoxy Facing Skins Bonded to a Gillcore® HK Honeycomb Core

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 3 - Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 0 - Minimal Hazard

Physical

: 0 - Minimal Hazard

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product